

DATASHEET

VECTRON POS M4



VECTRON

System concept

The Vectron POS M4 is a fully-fledged mobile POS system with all the functions of a stationary device. It works completely independent, i.e. without an additional server system. The ergonomically shaped touch system with TFT-LCD screen convinces with easy operation and fast order taking.

The robust POS system with powerful battery is protected against dust and water according to IP65 and is drop-proof up to 1.5 metres. Equipped with a built-in scanner, front and back camera, NFC, WLAN, Bluetooth, USB-C and Micro SD interfaces, the Vectron POS M4 is suitable for anyone who needs maximum flexibility.

The high-quality charging station for the Vectron POS M4 is suitable for safe storage of the POS system while charging the battery at the same time. The Vectron POS M4 can be operated in the station during the charging.

Hardware

Technical data of the Vectron POS M4 POS system

Display diagonal	140 mm (5.5")
Display type	TFT-LCD
Display lighting	LED
Display size (active)	124 x 62 mm
Display resolution	1440 x 720 Pixel
Input	Capacitive multi touch screen
Housing	two-piece plastic (IP 65)
Processor	ARM Cortex-A53 Quad-Core Processor; 2,0 GHz
Main memory	3 GB RAM
Mass storage	32 GB ROM
Interfaces	USB-C (OTG), 2-fold spring contact for charger, 8-fold spring contact for accessories, 1x Nano-SIM*, 2x PSAM*, 1x Micro-SD
Wireless network	IEEE 802.11 a/b/g/n/ac
Bluetooth	5.0
Camera	13 MP AF (rear)**, 2 MP FF (front) rear camera supports 1D/2D-barcode scanning
Scanner	Honeywell
NFC*	supported card types: A&B, Mifare, Felica
GPS	supports AGPS, GPS, Glonass, Baidou, Galileo
additional sensors	Acceleration, approach, light, compass
Audio	2 microphones, 1 loudspeaker
Tilt sensor	yes
Vibration alarm	integrated
Power supply	Lithium-polymer battery; 3,8 V / 5000 mAh
Temperature	Storage: -40 °C to +70 °C Operation: -20 °C to +55 °C Humidity: 5 to 95 %, non condensing
Dimensions (W x H x D)	74.6 x 154.4 x 17.1 mm
Weight	245 g
Certified	CE, UKCA
Warranty period	12 months of warranty
*	Currently not yet to be used.
**	Currently not yet to be used with the Vectron POS Android App.

Hardware

Technical data of the POS M4 battery

Type	Lithium-polymer battery
Charging capacity	5000 mAh
Voltage	3,8 V
Temperature	Storage: -40 °C to +70 °C Operation: -20 °C to +55 °C Humidity: 5 to 95 %, non condensing
Service life	up to 800 charge cycles
Dimensions (W x H x D)	70,8 x 52,9 x 10 mm
Weight	86 g

Software

usable software	Vectron POS Android App Vectron MobileApp
myVectron	Cloud-based myVectron services; integrated customer loyalty tools (e. g. individual campaigns, automatic processing of collection points, discount campaigns, vouchers)

Scope of delivery

Vectron POS M4

Standard shipment	Vectron POS M4 POS system Hand strap Plug-in power supply with cable POS M4 Battery Security and installation instructions
Optional accessories	Dual charging station for one Vectron POS M4 POS system and an additional battery POS M4 Battery Leather holster Belt Safety strap Stylus

Dimensions

Vectron POS M4
(W x H x D): 74.6 x 154.4 x 17.1 mm
2.9 x 60.8 x 6.7 inch



Vectron POS M4 Dual charging station
(W x H x D): 110 x 100 x 156 mm
4.3 x 3.9 x 6.1 inch



Vectron POS M4 Dual charging station incl. terminal POS M4 (W x H x D) : 110 x 196 x 156 mm, 4.3 x 7.7 x 6.1 inch

